


BERFIN H:205 CM REMOTE UPRIGHT DOOR FREEZER

alascold
REFRIGERATION

Technical Specifications



BERFIN Model remote multi - deck vertical deepfreezer provide the largest display space and enable the preservation of products for a long time while also saving energy and enabling easy use with their three-fold heated double - glazing doors which prevent clouding.



MODEL SIZE (INTERNAL) (MM)	1560	2344	3125	3905	
MODEL SIZE (EXTERNAL) (MM)	1660	2444	3225	4005	
COOLING CAPACITY (WATT)	TEMP CLASS : 3L2	936	1404	1872	2343
	TEMP CLASS : 3L1	1014	1521	2028	2538
EVAPORATOR HEATER (WATT)		166	183	216	250
TOP HEATER (WATT)		55	75	100	125
FRAME & DOORS CONSUMPTION (WATT)		583	858	1133	1408
DOOR NUMBER (PCS)		2	3	4	5
DISPLAY AREA (M ²)		2,45	3,67	4,90	6,13
VOLUME (M ³)		2,10	3,15	4,20	5,25
SHELVES LENGTH (PER LINE) (MM)		2x770	3x770	4x770	5x770
LIGHTING (WATT)		72	96	120	144
EVAPORATOR FAN NUMBER&WATT		3x43	4x43	5x43	6x43
AMBIENT CONDITION	@+25 °C / 60 % RH				
SHELVES DEPTH	5 x 570 mm				
SHELVES WEIGHT CAPACITY	200 kg / m ²				
NO OF ROW (INCLUDING BASE)	5				
DIGITAL CONTROLLER	ELIWELL ID SERIES / DIXELL				
SOLENOID VALVE	DANFOSS / OLAB / SANHUA				
EXPANSION VALVE	DANFOSS				

www.alaskasogutma.com



✉ info@alaskasogutma.com

☎ +90 (342) 328 94 04 (Pbx)

☎ +90 (342) 328 94 07

🏠 Aydınlar Mahallesi 03063 Nolu Cadde No: 23
27580 - Şehitkamil / Gaziantep / TURKEY




BERFIN H:220 CM REMOTE UPRIGHT DOOR FREEZER

alascold
REFRIGERATION

Technical Specifications



BERFIN Model remote multi - deck vertical deepfreezer provide the largest display space and enable the preservation of products for a long time while also saving energy and enabling easy use with their three-fold heated double - glazing doors which prevent clouding.



MODEL SIZE (INTERNAL) (MM)		1560	2344	3125	3905
MODEL SIZE (EXTERNAL) (MM)		1660	2444	3225	4005
COOLING CAPACITY (WATT)	TEMP CLASS : 3L2	1092	1638	2184	2734
	TEMP CLASS : 3L1	1170	1755	2340	2929
EVAPORATOR HEATER (WATT)		166	183	216	250
TOP HEATER (WATT)		55	75	100	125
FRAME & DOORS CONSUMPTION (WATT)		681	1002	1323	1788
DOOR NUMBER (PCS)		2	3	4	5
DISPLAY AREA (M ²)		2,77	4,17	5,56	6,95
VOLUME (M ³)		2,38	3,57	4,76	5,95
SHELVES LENGTH (PER LINE) (MM)		2x770	3x770	4x770	5x770
LIGHTING (WATT)		72	96	120	144
EVAPORATOR FAN NUMBER&WATT		3x43	4x43	5x43	6x43
AMBIENT CONDITION		@+25 °C / 60 % RH			
SHELVES DEPTH		6 x 570 mm			
SHELVES WEIGTH CAPACITY		200 kg / m ²			
NO OF ROW (INCLUDING BASE)		6			
DIGITAL CONTROLLER		ELIWELL ID SERIES / DIXELL			
SOLENOID VALVE		DANFOSS / OLAB / SANHUA			
EXPANSION VALVE		DANFOSS			

www.alaskasogutma.com



✉ info@alaskasogutma.com

☎ +90 (342) 328 94 04 (Pbx)

☎ +90 (342) 328 94 07

🏠 Aydınlar Mahallesi 03063 Nolu Cadde No: 23
27580 - Şehitkamil / Gaziantep / TURKEY

